



EXPERIENCE AND HIGH TECHNOLOGY FOR YOUR SURFACE DRESSINGS

Mounted on 4, 6 or 8 wheeler truck and semi-trailer




SPRAYING OF QUALITY FOR YOUR SURFACE DRESSING

- Telescopic spray bar made of 3 arms: width from 4.4 to 6.2 m; dosage from 0.2 to 2.5 L/m²
- Shock sensors
- · Stainless steel pneumatic jets, removable, 100 mm centerline for a triple overlap on the ground
- Border jets
- 3 spraying modes: fixed; jet by jet;
- Automatic switch between 1 jet upon 2 and 1 jet upon 3 for low dosages
- · Hand lance
- Optional: remote control; additive device (single or double); bi-dosage for tyre treads; lime milk







TANK / HEATING , **BINDER DISTRIBUTION**

- Elliptical ADR tank, insulated, from 7 000 to 23 000 L
- · Direct or thermic-oil heating, with automatic fuel burner
- Binder distribution (pump, filter, valves...) with access from the ground
- 50 m³/h heated binder pump
- Pneumatic valves block (BVX) for binder distribution
- Optional: not ADR, overnight heating, sacrificial anodes



SECURIT RESPECT OF THE ENVIRONMENT

- All spraying and cleaning operations managed from the cab
- Filling dome access with secured platform
- Care and maintenance designed from the conception of the machine
- Elements positioned consistently and all accessible from the ground
- Automatic cleaning device without any binder rejection on the ground
- Jobs and consumptions follow up
- Rear view camera



COMPUTER NEW GENERATION: CLEV'ER

- navigation, ergonomic control with touch screen
- Binder dosage programming
- · Binder pump automatic regulation
- Truck engine regulation for optimum work speed

- Computer Clev'ER in cab: tablet, easy Individual jet On/Off by touch screen
 - · Connected device for achiving and monitoring of job data

