



ACMAR



BINDER SPRAYER

EXPORT - 417

Tel. +33 (0)2 43 06 14 28
info@acmar.fr

acmar.fr



EXPERIENCE AND HIGH TECHNOLOGY FOR YOUR SURFACE DRESSINGS

Mounted on 4, 6 or 8 wheeler truck



A SPRAYING OF QUALITY FOR YOUR SURFACE DRESSING

- 3 arms spray bar : width from 3.2 à 4.4 m ; dosage from 0.2 to 2.5 L/m²
- Manual opening extensions
- Up/down hydraulic rising
- Stainless steel pneumatic jets, removable, 100 mm centerline
- Automatic switch between 1 jet upon 2 and 1 jet upon 3 for low dosages
- Hand lance



STORAGE / HEATING / BINDER DISTRIBUTION

- Insulated all binders tank (bitumen and emulsion) from 5 000 to 18 000 liters
- Direct heating with automatic fuel burner
- 50 m³/h heated binder pump
- Binder suction with pneumatic valves bloc
- Pneumatic valves block for binder circulation
- Option : hydraulic power driven by auxiliary engine



SECURITY / MAINTENANCE

- Filling dome access with secured platform
- Care and maintenance designed from the conception of the machine
- Elements positioned consistently and all accessible from the ground
- Automatic cleaning process without any binder rejection on the ground
- Optional : rearview camera



SMART16 COMPUTER

- SMART16 computer in the cab with controls on ergonomic arms and rear panel control
- Programming of binder dosages
- Controls on rear platform
- Binder pump speed
- Individual jets On/Off (with switches)
- Archiving and monitoring of jobs data (surface, dosage, job name...)
- Optional : printer