



EXPERIENCE AND HIGH TECHNOLOGY FOR YOUR SURFACE DRESSINGS

Mounted on 4 wheeler truck from 16 to 19 T GVW



SPRAYING OF QUALITY FOR YOUR URFACE DRESSING AND PATCHING

- · Insulated emulsion tank of 4 000 L
- · Direct heating with automatic fuel burner
- · 35 m³/h heated binder pump
- · 3m spray bar with hydraulic opening (2 extensions)
- · Stainless steel pneumatic jets, removable, 125 mm centerline
- · Dosage from 0.2 to 2.5 L/m²
- · Hand lance





HIGH QUALITY CHIPPINGS SPREADING

- · 4,5 m³ fixed hopper
- 3 m automatic chippings spreader with 2 telescopic extensions
- Chippings from 2 to 15 mm
- Dosage from 2,5 L/m² to 16 L/m²
- Chippings boxes for shovel
- Optional: 3,5T and/or heavy duty hook



SECURITY MAINTENANCE RESPECT OF THE **ENVIRONMENT**

- Filling dome access with safe platform
- Care and maintenance designed from the conception of the machine
- Elements positioned consistently and all accessible from the ground
- Automatic cleaning device without any binder rejection on the ground
- Optional: rearview camera





SMART₁₆ COMPUTER

- SMART16 computer in the cab with controls on ergonomic arm
- Programming of binder dosages
- Binder pump speed
- Individual jet and date On/Off through switches box

- Archiving and monitoring of jobs data (surface, dosage, job name...)
- Optional : printer ; sighting device for patching

MAWA AAAA

AAAA VAVA AAAA

AAAA

AAAA

AAAA

AAAA VAVA

AAAA

AAAA AAAA